



Product Service

CERTIFICATE

No. Z2 118443 0037 Rev. 10

Holder of Certificate: **Jinko Solar Co., Ltd.**
No.1, Yingbin Road, Economic Development Zone
334100 Shangrao City, Jiangxi
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062307437-10

Valid until: 2030-01-21

Date, 2025-01-24

(Zhulin Zhang)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

CERTIFICATE

No. Z2 118443 0037 Rev. 10

Model(s):

JKMxxxN-78HL4-BDV, JKMxxxN-78HL4-BDV-J,
 JKMxxxN-78HL4-BDV-IN (xxx=600-665, in steps of 5)
 JKMxxxN-72HL4-BDV, JKMxxxN-72HL4-BDV-J,
 JKMxxxN-72HL4-BDV-U, JKMxxxN-72HL4-BDX,
 JKMxxxN-72HL4-BDV-IN (xxx=560-610, in steps of 5)
 JKBSxxxN-48HL4-BDV (xxx=375-390, in steps of 5)
 JKMxxxM-72HL4-BDVP, JKMxxxM-72HL4-BDVP-J
 (xxx=540-560, in steps of 5)
 JKMxxxN-66HL4M-BDV, JKMxxxN-66HL4M-BDX
 (xxx=590-650, in steps of 5)
 JKMxxxN-54HL4M-BDV (xxx=495-530, in steps of 5)
 JKMxxxN-48HL4M-BDV (xxx=440-470, in steps of 5)
 JKMxxxN-54HL4R-BDV, JKMxxxN-54HL4R-BDB
 (xxx=420-460, in steps of 5)
 JKxxxN-66H5-BGV, JKMxxxN-66HL5-BDV
 (xxx=685-730, in steps of 5)
 JKBSxxxN-48HL4-BDVW (xxx=370-390, in steps of 5)
 JKMxxxN-54HL4R-DB (xxx=435-455, in steps of 5)
 JKMxxxN-48HL4M-DB (xxx=440-465, in steps of 5)
 JKMxxxN-48HL4M-DV (xxx=440-470, in steps of 5)
 xxx is standing for rated output power at STC

Parameters:

Fire Safety Class:	Class C according to UL790
Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed or frameless double glass with Junction box, cable and connector.

Production

Facility(ies):

105416, 115863, 115864, 115876, 113943
 118443, 116025, 119488, 075612, 121280,
 115860, 115862, 122742, 118612, 119487,
 125355, 120017, 124145

Tested according to:

IEC 61215-1:2021
 IEC 61215-1-1:2021
 IEC 61215-2:2021
 IEC 61730-1:2023
 IEC 61730-2:2023
 EN IEC 61215-1:2021
 EN IEC 61215-1-1:2021
 EN IEC 61215-2:2021
 EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06